U. S. DEPARTMENT OF COMMERCE

Technical News Bulletin

of the

National Bureau of Standards

★ *Issued Monthly* ★

Washington | December 1940[1] | Number 284

CONTENTS

Revised standard frequency broadcasts.
Alternating-current grounds on water pipes.
Bonding joints in pipe lines for cathodic protection.
Effect of low temperatures on the properties of aircraft metals.
A photometric procedure using barrier-layer photocells.
Use of azeotropic distillation in separating petroleum hydrocarbons.
Standard electrode potential of sodium.
Preparation of benzoic acid of high purity.
Solution of osmiridium and other refractory materials in acids at high temperatures.
Standard color test for porcelain enamels.
Specific refraction and dispersion of glasses.
Pore system in bricks and its relation to frost action.
Weathering tests of asphalt shingles.
Strength and elongation of silk yarns as affected by humidity.
New and revised publications issued during November 1940.
Mimeographed material: Letter Circulars.
Recent Bureau articles appearing in outside publications.
Index to Technical News Bulletin 1940, Numbers 273 to 284, inclusive.

REVISED STANDARD FREQUENCY BROADCASTS

The Bureau's standard frequency station, WWV, was destroyed by fire November 6. A temporary transmitter has been established in another building and has begun a reduced service. It broadcasts the frequency 5 megacycles (5,000 kilocycles) per second, every day (except Sunday) from 10 a. m. to midnight. This is continuous wave only, with telegraphic code announcements of the call letters WWV every 20 minutes. The accuracy of the frequency is the same as in the past, namely, better than a part in 10 million.

The broadcast is from a 1-kilowatt transmitter. Generally speaking, it is most useful for moderate distances in the daytime and long distances at night. More precisely, for reception in locations reasonably free from interference, it is receivable at all distances up to 1,000 miles from Washington in the middle of the day. The distance range increases after about 4 p. m. (EST) until at night the broadcast is receivable throughout the United States; sometimes at night it may be difficult to receive it at distances between 50 and 500 miles, while it is easy to receive it beyond 500 miles. In the spring the daytime distance range will decrease, dropping to about 500 miles in the summer.

This restricted service will continue for some months. As rapidly as possible a new station will be established to provide more fully than in the past, standard frequencies receivable at all times throughout the country. These will include standard radio frequencies, standard seconds pulses, and the standard of musical pitch, 440 cycles per second, which will unfortunately not be available during the period in which the temporary transmitter is used.

[1] Published with approval of the Director of the Budget.

276551—40

ALTERNATING-CURRENT GROUNDS ON WATER PIPES

The technical subcommittee of the American Research Committee on Grounding has been investigating complaints covering damage to water systems in houses and pollution of water flowing in the pipes. The Bureau is represented in this work by Morton G. Lloyd, Chief of the Safety Codes Section.

The subcommittee has issued a summary report covering 21 complaints in 7 communities, showing that in none of these cases was there evidence to indicate that the flow of alternating current over water pipes or mains by itself has caused damage to the piping or to the water flowing in the pipes. On the other hand, the investigations revealed differences in the chemical composition of the water supplied to a given user; differences in impurities of the metal of which the pipes are made; galvanic action resulting from the indiscriminate use of many different metals, and variations in their composition; differences in the temperature of the hot water supply, and in the rate and amount of water drawn from the mains; and many other factors.

It has not been possible to develop thoroughly all of the complex variables present in the different situations investigated, and definite conclusions are rendered more difficult because of the inability of the subcommittee to obtain more cases for investigation. It is, therefore, not possible at this time to state that damage from alternating current flowing over water pipes could not occur.

For the future, the Grounding Committee expects to continue its investigation of all complaints of water contamination where grounding of electric circuits is involved, to determine, if possible, whether there is any relation in normal practice between superimposed alternating currents and effects on water pipes and the water itself. The committee also proposes to establish simple test set-ups where accelerated reactions might be obtained if such a relation does exist. These set-ups would be of such a nature as not to require continuous observation, but would be placed in water plants or laboratories where occasional checks could be made under the supervision of skilled personnel. However, the necessity for prompt investigation of all complaints would still exist, so as to gain field experience and to correlate the various factors involved.

BONDING JOINTS IN PIPE LINES FOR CATHODIC PROTECTION

During the past few years the use of electrical or cathodic protection to prevent the corrosion of pipe lines has increased rapidly. On lines joined by mechanical couplings, one of the chief items of cost in installing the protective system is that of bonding across the couplings. These bonds are not always successful; some of them become detached from the pipe.

An investigation was made by Scott Ewing, research associate of the American Gas Association, of the methods that might be used to attach copper bond wires to steel pipes. This involved reviewing the experience of railroads in bonding rails; investigating the methods of soldering, brazing, and welding; and obtaining information from pipe-line engineers on their bonding experience.

Although soldered joints have less strength than those made by any other method, and they have been unsuccessful on electric railroads, they have been satisfactory on many cathodic protection systems. The greatest difficulty has been experienced with brazed joints, although copper strips, welded to the pipe, have proved successful. While any of the above methods of joining will probably be satisfactory if the work is properly done, the cost of installing the bonds is likely to be high with some methods, and at times it is extremely difficult to make a good joint in the field.

It is believed that a cheaper and more dependable bond will be obtained by the use of steel terminal copper bonds than by any other means. Tests are now being made which it is hoped will lead to the development of such a terminal. These bonds can be manufactured by methods similar to those used for rail bonds; and if the demand for them is sufficient, their moderate price should make the total cost of the installation lower than that of any other type of pipe-line bond.

EFFECT OF LOW TEMPERATURES ON THE PROPERTIES OF AIRCRAFT METALS

Because of the lack of essential information on the mechanical properties of aircraft metals at low temperatures, the subject was investigated by Samuel J. Rosenberg, of the Bureau's Metallurgy Division, and the findings will be published in the December Journal of Research (RP1347).

Practically all metallic alloys used in aircraft construction were investigated. These were divided into three classes: (1) Ferritic steels, (2) austenitic stainless steels and nickel alloys, and (3) light metal alloys (aluminum- and magnesium-base). The effect of temperatures down to —78° C (—108° F) upon the tensile properties, hardness, and impact resistance of these materials was determined.

It was found that low temperature had no bad effect on any of these properties, with the exception of the impact resistance of the ferritic steels. In the case of these steels, a decrease in impact resistance occurred as the test temperature was lowered.

A PHOTOMETRIC PROCEDURE USING BARRIER-LAYER PHOTOCELLS

The introduction in recent years of light sources of various colors, such as fluorescent lamps, has brought up the problem of measuring their candlepower. In the Journal of Research for December (RP1348), Louis E. Barbrow describes a procedure in which photoelectric cells of the barrier-layer type are used for measuring the candlepower of such light sources. These photoelectric cells have been corrected so as to have a spectral response simulating that of the average eye. Any remaining difference of spectral response between the cell and the average eye is compensated by the use of filters. Results obtained in the photometry of vacuum and gas-filled tungsten-filament lamps and "white" and "daylight" fluorescent lamps, and in the determination of the transmission factors of colored filters are given.

USE OF AZEOTROPIC DISTILLATION IN SEPARATING PETROLEUM HYDROCARBONS

At the annual meeting of the American Petroleum Institute, in Chicago, a paper was presented on November 13 before the Division of Refining entitled "The use of azeotropic distillation in separating hydrocarbons from petroleum", by Frederick D. Rossini, Beveridge J. Mair, and Augustus R. Glasgow, Jr., of the American Petroleum Institute Research Project 6 at the Bureau. The paper contains a discussion of the principles involved in azeotropic distillation, the substances that form azeotropic mixtures with hydrocarbons and their selection, and the separation of hydrocarbons by azeotropic distillation, including aromatics from naphthenes and paraffins, naphthenes from paraffins, aromatics of different degree of "aromaticity", and one-ring naphthenes from poly-ring naphthenes. The benefits accruing as a result of systematic and efficient distillation at a reduced pressure, prior to the azeotropic distillation, are pointed out. A general procedure is outlined for separating a given fraction of petroleum (gasoline or kerosene) by distillation alone, in its several variations of distillation at normal pressure, distillation at reduced pressure, and distillation with an azeotrope-forming substance. The hydrocarbons which can be separated from petroleum in a substantially "pure" state by distillation alone are listed, and several practical applications of azeotropic distillation are mentioned.

STANDARD ELECTRODE POTENTIAL OF SODIUM

The reaction of the alkali metals with water disturbs the equilibrium conditions necessary for direct measurements of their electrode potentials. An indirect method which overcomes this difficulty depends on the possibility of measuring (a) the potential of a dilute amalgam of the alkali metal with respect to an aqueous solution of its ions and a reference electrode, and (b) the difference in potential between the same amalgam and the pure metal when both are immersed in a nonaqueous conducting solution containing ions of the alkali metal. By this method the standard electrode potentials of the alkali metals have all been measured. However, these measurements have usually involved the introduction of one or more of the uncertainties caused by the use of liquid junctions, solutions for which the activities can only be approximated, and unreliable reference electrodes. RP1350 in the December Journal of Research gives the results of a redetermination by Edgar Reynolds Smith and John Keenan Taylor of the standard electrode potential of sodium, in which these sources of possible error were eliminated. The two cells measured may be represented by

$$\mathrm{Na(s)\ ;\ NaI(in\ dimethylamine)\ ;\ Na(amalgam)}$$

and

$$\mathrm{Na(amalgam)\ ;\ NaCl}(m), \mathrm{AgCl(s)\ ;\ Ag(s)}.$$

The standard electrode potential Na(s) ; Na^+ was obtained over the temperature range of 5° to 40° C. The final results may be expressed by the equation

$E° = 2.71324 + 0.0007532\ (t - 25) + 0.000000688\ (t - 25)^2$, in which $E°$ is in international volts and t is in degrees centigrade.

PREPARATION OF BENZOIC ACID OF HIGH PURITY

In the Journal of Research for December, Frank W. Schwab and Edward Wichers describe (RP1351) the preparation of benzoic acid of extremely high purity.

For many years benzoic acid has been used as a standard substance in acidimetry and for the calibration of bomb calorimeters. Certified samples of the material have been issued by the Bureau since 1911. Recently, it became necessary to prepare some of the material of the highest practicable purity, primarily for a determination of the heat of combustion of the pure substance.

A number of methods for preparing pure benzoic acid were compared, both with respect to the degree of purity and the ease with which it could be attained. Simultaneously, a study was made of means for determining the purity of the substance. The methods adopted for determining purity were based on very precise determinations of the freezing range of the acid and on measurements of the specific heat of the solid substance at temperatures closely approaching its melting point.

The methods of preparation which were studied were: Purification of a commercial material, which was about 99.98 percent pure, by fractional distillation in vacuum; fractional freezing, and crystallization from solvents; and preparation from other substances by selected reactions. A purity of 99.999 mole percent was attained by each of three methods: Crystallization from benzene; fractional freezing; and hydrolysis of benzoyl chloride, purified by fractional distillation. Crystallization from water gave material 99.996 percent pure in the same number of steps that yielded the purer material by crystallization from benzene. The ready availability of pure water partly offsets the advantage of the more rapid purification from benzene. Hydrolysis of benzoyl chloride is rapid and easy, but involves painstaking preliminary purification of the parent substance. Fractional freezing is a relatively simple and rapid method. The freezing point of benzoic acid is tentatively given as 122.36°±0.01° C.

SOLUTION OF OSMIRIDIUM AND OTHER REFRACTORY MATERIALS IN ACIDS AT HIGH TEMPERATURES

Osmiridium, a natural alloy of metals of the platinum group, is the principal source of the rare but important metal iridium, which at present market values commands about four times the price of platinum. This mineral is relatively abundant in the Alaskan platinum deposits which constitute the only important platinum-metal resource of the United States. Determination of its iridium content has been one of the analyst's most difficult problems, in part because the native alloy is so hard to get into solution.

In usual practice, osmiridium is brought into solution for analysis by a laborious treatment with alkaline oxidizing fluxes. The other alloys found in the native platinum minerals can be dissolved rather readily by means of the mixture of hydrochloric and nitric acids known as aqua regia. At temperatures up to 100°C, above which it cannot be used in open vessels, aqua regia is entirely without effect on the osmiridium. At temperatures approaching 200° the acid mixture begins to attack the alloy, and at 250° to 300° C the attack is rapid enough to afford a practicable means of dissolving the material preparatory to analysis. Iridium, by itself, is dissolved somewhat more slowly than osmiridium, and the metals osmium, ruthenium, and rhodium more rapidly. The treatment as developed by E. Wichers and W. G. Schlecht, of the Bureau's Chemistry Division, is conducted in a sealed glass tube enclosed in a steel shell which is charged with compressed air to offset the high pressures (as high as 3,000 lb/in^2) developed by the acid mixture.

The rate of attack varies greatly with the composition of the acid mixture as well as with the temperature. At present a mixture of 20 volumes of concentrated hydrochloric acid and 1 volume of fuming nitric acid, at a temperature of about 275° C, is recommended; but work now in progress may disclose better operating conditions. One or two days may be required for complete solution, depending upon the size of the grains, but the operation requires no attention during that time. About 20 milliliters of the acid mixture is needed to dissolve 1 gram of osmiridium. When the sample is dissolved, the tube is cooled with dry ice before opening it, to prevent loss of any volatile substances, such as osmium tetroxide.

Certain other materials which have been troublesome to get into solution for analysis respond to the same kind of treatment. Examples are sintered aluminum and beryllium oxides, many silicate rocks, and complex rare-metal alloys containing chromium, molybdenum, tungsten, etc. For some of these substances hydrochloric acid is used rather than aqua regia. Outstanding advantages of the method are that only volatile reagents are used and that contamination of the sample with impurities from reagents is minimized.

STANDARD COLOR TEST FOR PORCELAIN ENAMELS

For several years the Bureau has cooperated with the Porcelain Enamel Institute in developing standard tests for porcelain enamels. One current project is a standard test for evaluating color differences between nearly identical specimens. For this work a special subcommittee of the Institute was formed, members of which prepared 15 sets of 13 specimens each. Every set consisted of a central standard and 12 other specimens having slight, systematic differences from the standard in their hue saturation and lightness. The colors of the central standards were widely varied within the possible range.

Visual estimates of the directions and magnitudes of the differences between the central standards and the similarly colored specimens in the respective sets have been made at the Bureau and at several cooperating laboratories. Additional estimates are planned. Several different means of determining these differences by computation from data obtained on various instruments are also being tried. It is planned to modify the formulas or, if necessary, one or another of the instruments, until reasonably good agreement between such determinations and the averages of visual estimates can be obtained. If this can be done successfully, the instrumental method will be recommended as standard, and can be used both as a control method for manufacturers and a test method for purchase specifications.

SPECIFIC REFRACTION AND DISPERSION OF GLASSES

Recently John C. Young and Alfred N. Finn, Chief of the Bureau's Glass Section, have made many new glasses of unusual composition, containing, in varying amounts, such elements as rubidium, cesium, gallium, yttrium, indium, lanthanum, cerium, praseodymium, neodymium, samarium, gadolinium, holmium, erbium, columbium, tantalum, etc. Refractive index and density data on these glasses, as well as similar data from the literature on the ordinary constituents of glass, have been examined statistically to determine the applicability to glass of several of the better known specific refraction ratios. It was found that of these ratios only the Gladstone-Dale ratio possesses each of the following features: For any specified wavelength of light it is independent of the thermal history of a given glass, and it varies linearly with composition. It is also useful, in combination with "specific dispersion", for computing the μ-value, or "dispersive index", of a glass.

In RP1352, which will be published in the December number of the Journal of Research, definite numerical factors are given for 32 glass-making oxides, from which one can compute the specific refraction as well as the dispersive index, or μ-value, of a glass composed entirely of any or all of these oxides. These factors are shown to be related to the periodicity of the elements. The ability to predict the dispersive index (μ) of a glass should be of considerable interest to optical glass manufacturers, because it will assist them in designing better glasses for telescopes, binoculars, cameras, etc.

PORE SYSTEM IN BRICKS AND ITS RELATION TO FROST ACTION

Certain properties associated with the porous structure of bricks have an important bearing on their durability when exposed to the weather. These properties have received scant attention heretofore, and an investigation was made by Ray T. Stull and Paul V. Johnson to obtain data on these properties and on their relation to the failure of bricks as a result of freezing and thawing. Seven series of bricks, the products of five different manufacturers, were selected to represent ranges in hardness, methods of manufacture, and temperature at which they had been burned. The properties determined were: Percentage of porosity; variation in porosity within a brick; permeability to air and water; the flow of air through two members in series; effect of time, under continuous flow, on the water permeability; the mean capillary radius and the number of capillaries in an ideal structure which would have the same permeability as that determined experimentally for the brick; saturation coefficient by 48 hours' im-

mersion; increase in saturation coefficient with repeated freezing and thawing, and the resistance of bricks to failure by repeated freezing and thawing.

The variation in porosity of a brick is partly responsible for its lack of uniform structure and is, therefore, a contributing factor affecting its life when subjected to repeated freezing and thawing.

No definite correlation was found as to location of lowest, medium, and highest porosities of individuals among the bricks tested. The differences between maximum and minimum percentage porosities of the different sections of the individual bricks ranged from 2.8 to 10.4, a spread of 11.6 to 48.4 percent.

When the air-permeability values, f_1 and f_2 of two members composing a unit, and their relative thicknesses, T_1 and T_2, are known, the air conductance, F, of the unit can be determined by application of the equation.

$$F=\frac{f_1 f_2}{f_1 T_2+f_2 T_1}.$$

The differences between the calculated and experimental F values determined were so small as to be negligible.

The mean effective capillary radius, permeability, and number of cycles of freezing and thawing to cause failure of the bricks increase, and the pore volume, number of capillaries, and saturation coefficient decrease with increase in burning temperature. The decrease in pore volume and number of pores indicates that some pores have become filled or sealed and, therefore, inactive so far as permeability and absorption are concerned. The increase in mean effective capillary radius and decrease in number of capillaries indicate that the pores rendered inactive were chiefly the smaller ones originally occurring as microcavities formed by the microparticles.

The air permeabilities were constant with respect to time of flow, whereas the water permeabilities varied, increasing with time for those bricks having mean capillary radii less than 2 microns and decreasing for those with radii greater than 2 microns.

The saturation coefficient increases with increase in the number of freezing and thawing cycles. The relation between these two variables appears to be hyperbolic in character, and may be expressed empirically by the equation

$$S=a-\frac{K}{b+C},$$

where S is saturation coefficient, C, the cycles of freezing and thawing and a, b, and K are constants for a definite brick but different for different bricks. The constant a represents (theoretically) the upper limiting value of the saturation coefficient under the assumption that the brick would stand an infinite number of freezing and thawing cycles.

Bricks considerably laminated may attain saturation coefficients greater than unity by repeated freezing and thawing, thus containing larger volumes of water than their initial pore volumes.

The general trend of the data indicates that the number of cycles of freezing and thawing to cause failure of the brick increases when the permeability and effective capillary radius increase, and when the porosity, number of capillaries, and saturation coefficient decrease.

The Journal of Research for December will contain the complete account of this investigation, which will be published as RP1349.

WEATHERING TESTS OF ASPHALT SHINGLES

Recent experimental work on the absorption of water by asphalt shingles has led to the development of a new blistering test. In the usual procedure, the shingle is immersed in water for a short time and is then subjected to a temperature of 221°F for 1 hour. Experimental data showed this test to be wrong in principle, as it did not take into consideration the "breathing action" of the shingles. A new test was therefore devised which takes this "breathing" into account. In this test the specimen is subjected to a certain set of conditions which is repeated daily for about a week. The specimen is never exposed to a temperature higher than 194°F.

STRENGTH AND ELONGATION OF SILK YARNS AS AFFECTED BY HUMIDITY

The strength of silk hosiery yarns is not significantly affected by changes in relative humidity of the surrounding air between 33 and 55 percent, but the strength is less when the relative humidity is above these limits. Maximum strength at these humidities is obtained with yarns having a twist of approximately 15 turns per inch, according to E. Max Schenke, Director of Research, and Howard E. Shearer, Research Associate, of the National Association of Hosiery Manufacturers, who have been studying this matter at the Bureau. A report of the results of their studies will appear as RP1353 in the December issue of the Journal of Research.

The yarns studied varied in number of threads from 2 to 9, and in number of turns of twist per inch from 5 to 36. They were tested for breaking strength and breaking elongation at 70°F after various periods of exposure in relative humidities from 33 to 86 percent. The elongations of the yarns increased with an increase in relative humidity of the air. The elongation, on the average, increased 1 percent with increase in relative humidity from 33 to 43 percent, and 1.9 percent with an increase in relative humidity from 76 to 86 percent. The average strength of all yarns was 3.41 grams per denier when tested under standard conditions.

NEW AND REVISED PUBLICATIONS ISSUED DURING NOVEMBER 1940

Journal of Research [2]

Journal of Research of the National Bureau of Standards, volume 25, number 4, October 1940 (RP1333 to RP1340, inclusive). Price 30 cents. Annual subscription, 12 issues, $3.50.

Research Papers [2]

[Reprint from the September 1940 Journal of Research]

RP1326. Pectic substance of cotton fibers in relation to growth. Roy L. Whistler, Albert R. Martin, and Carl M. Conrad. Price 5 cents.

Commercial Standards [2]

CS80–41. Electric direction signal systems other than semaphore type for commercial and other vehicles subject to special motor-vehicle laws (after market.) Price 5 cents.

CS85–41. Electric license-plate lamps for vehicles (after market). Price 5 cents.

CS86–41. Electric stop lamps for vehicles (after market). Price 5 cents.

CS88–41. Liquid-burning flares. Price 5 cents.

Technical News Bulletin [2]

Technical News Bulletin 283, November 1940. Price 5 cents. Annual subscription, 50 cents.

[2] Send orders for publications under this heading only to the Superintendent of Documents, Government Printing Office, Washington, D. C. Subscription to Technical News Bulletin, 50 cents per year; Journal of Research, $3.50 per year (to addresses in the United States and its possessions, and to countries extending the franking privilege); other countries, 70 cents and $4.50, respectively.

MIMEOGRAPHED MATERIAL

Letter Circulars

[Letter Circulars are prepared to answer specific inquiries addressed to the National Bureau of Standards and are sent only on request to persons having definite need for the information. The Bureau cannot undertake to supply lists or complete sets of Letter Circulars or send copies automatically as issued.]

LC608. Detergents and related subjects. (Supersedes LC403.)

LC610. Electric batteries and standard cells: Publications by the staff of the National Bureau of Standards and references to other sources of information. (Supersedes LC553.)

LC612. List of Simplified Practice Recommendations. (Supersedes LC594.)

LC616. Etching of designs and lettering on metals.

RECENT BUREAU ARTICLES APPEARING IN OUTSIDE PUBLICATIONS [3]

API pipe-coating tests—final report. Kirk H. Logan. Preprint, paper before twenty-first annual meeting, Am. Petroleum Institute (250 Park Ave., New York, N. Y.) (Nov. 14, 1940).

Introductory dialogue for a symposium on spectrophotometry in the pulp and paper industries. Deane B. Judd and L. C. Lewis. Paper Trade J. (10 E. 39th St., New York, N. Y.) 111, TS133 (Sept. 5, 1940).

Survey of spectrophotometers. Kasson S. Gibson. Paper Trade J. 111, TS135 (Sept. 5, 1940).

Systematic color designations for paper. Deane B. Judd. Paper Trade J. 111, TS201 (Oct. 17, 1940).

Sorption of water by plastics. G. M. Kline, A. R. Martin, and W. A. Crouse. Modern Plastics (122 E. 42nd St., New York, N. Y.) 18, 119 (Oct. 1940).

The transformation of austenite. T. G. Digges. Metal Progress (7301 Euclid Ave., Cleveland, Ohio) 38, 419 (Oct. 1940).

Oxides extracted in Merriman's test of portland cement. E. P. Flint and P. H. Bates. Rock Products (330 So. Wells St., Chicago, Ill.) 49, No. 10, 46 (Oct. 1940).

[3] These publications are not obtainable from the Government. Requests should be sent direct to the publishers.

INDEX TO TECHNICAL NEWS BULLETIN 1940
NUMBERS 273 TO 284, INCLUSIVE

A

Page

Absolute electrical units, time of introduction 1
Absolute standard of mutual inductance 49
Absorption of water by plastics 74
Acid, combination of wool protein with 26
Acid, *d*-galacturonic, improvements in preparation 66
Acid-resisting portion of porcelain enamel coatings, thickness 49
Acoustic materials, effect of painting on sound absorption 43
Acoustical Society of America, meeting 48
Adhering liquid film, thickness 76, 92
Admixtures, effect on temperature rise and time of set of cement pastes 87
Air-conditioning equipment, corrosion inhibitors 50
Air-conditioning of materials, equipment for 51
Air infiltration through windows 61
Aircraft metals, corrosion 56
Aircraft metals, effect of low temperatures **106**
Aircraft pressure-measuring instruments, corrugated metal diaphragms for 8
Air-setting strength of refractory mortars 43
Aliphatic hydrocarbons, physical properties 7
Alkalies, determination of, in cement 100
Alternating-current grounds on water pipes 106
Alternating-voltage compensator, vacuum tube 59
Aluminum alloys, wrought, corrosion characteristics 77
American Lumber Standards 61
American Physical Society meeting 39
Aneroid diaphragm capsule 9
Argyria—the pharmacology of silver, book on 2
Arrestment, balance, faulty 56
Arsenic, colorimetric determination 7
Ash, in textile fibers, estimation by electrodialysis 59
Asphalt shingles, weathering tests **110**
Austenitic grain size, effect of heating rate 66
Automobile mileage, effect on octane number requirement 17
Automobiles, 1939, fuel requirements 17
Aviation fuel, optimum 7
Azeotropic distillation in separating petroleum hydrocarbons **107**

B

Balance arrestment, faulty 56
Barrels, silver-lined 27
Base, combination of wool protein with 26
Baths, cyanide plating 77
Batteries, storage, effects of cobalt and nickel 85
Batteries, storage, energy relations 35
Bearce, Henry W., heads division of weights and measures 40
Bearings, journal, load-carrying capacity 40
"Bender steel home" wall construction, structural properties 4
Benzoic acid of high purity, preparation 108
Bifilar mutual inductance 49
Boilers, heating, effect of soot on rating 90
Boiling points of heptane and isooctane 25
Bonding joints in pipe lines 106
Book cloths, commercial standard 90
Brake linings, machine for testing 40
Brazil, certification of weighing and measuring apparatus for 84
Brick-concrete-block wall constructions, tests 5
Brick, paving, simplified practice recommendation 91
Brick wall construction, Munlock 79
Brick walls, water-tightness 4
Bricks, pore system in relation to frost action 109
Bridge, dual, for measurement of inductance 59
Brightness meter, portable, for luminous preparations 85
Broadcast, standard frequency, revised 105
Bromine, reaction with furfural and related compounds 19
Bronze, effect of, on marble 6
Builders' hardware (nontemplate) 91
Building board, fiber, stability 60
Building codes, what is the matter with 32
Building construction, wood frame, "Palisade Homes" 44
Building constructions, wood frame, using "Red Stripe" lath 24
Building granites, properties 68
Burners, oil, automatic mechanical draft, commercial standard 8
Bushel weights, legal, for various commodities 31

C

Calking materials, plastic 32
Candlepower, measuring with photocells 107
Cans, silver lined 2, 27
Capsule, aneroid diaphragm 9
Carbon paper and typewriter ribbons 61
Cartons and molds, ice-cream brick 92
Cathode films, composition 57
Cathodic protection of pipe lines, bonding joints for 106
Cations, effect of, on physical properties of ball clays 101
Ceiling insulation, effectiveness 88
Cells, soil-corrosion, electrode potentials and polarization 85
Cellulosic materials, determination of uronic acid 7
"Celotex" insulating boards with wood-frame wall and partition construction 52
Cement clinker, glass in 5, 75
Cement, dental silicate 58
Cement, determination of alkalis in 100
Cement pastes, temperature rise and time of set 87

Page

Ceramic materials, decomposition for chemical analysis 75
Ceramic whiteware, moisture expansion 88
Certificates of National Bureau of Standards recognized in Brazil 84
Chemical glassware, removal of static charge 66
Chinaware, chipping resistance 6
Chipping resistance of chinaware 6
Chromium coatings, outdoor exposure tests 36
Chromium coatings, thickness, spot test for 57
Chromium-vanadium steels, thermal expansion 3
Circuit, integrating, for tube counters 78
Clay materials, heated, nature of glass phase in 57
Clay, whiteware and body, length changes 57
Clays, ball, effect of cations on physical properties 101
Cloths, book, commercial standard 90
Coatings on underground pipe lines 16, 96
Coatings, silver, for containers 36
Cobalt and nickel, effects of, in storage batteries 85
Codes, building, what is the matter with 32
Color grading of papers by spectrophotometry 34
Color test for porcelain enamels 109
Colorimetric determination of arsenic 7
Colors, surface 27
Commercial standard for automatic mechanical draft oil burners 8
Commercial standard for fuel oils, revised 52
Commercial Standard for hardwood interior trim and molding 15
Commercial standard for sun glasses 44
Commercial standards and their value to business 70
Compensator, a vacuum-tube alternating-voltage 59
Compressive tests of thin materials, extension of "pack" method 78
Concrete block wall constructions 5
Concrete Masonry Association, National, meeting 24
Concrete, moisture conditions in 87
Concrete wall units, Knap 43
Conditioning paper for multicolor offset printing 15
Conductor pipe and eaves trough, simplified practice recommendation 44
Conference of State utility commission engineers 48
Conference on Weights and Measures, Thirtieth National 40
Cooling rate, critical, of iron-carbon alloys 50
Copper citrate, alkaline, reducing powers of sugars with 27
Copper tubing, soft soldered joints in 96
Corrosion characteristics of wrought aluminum alloys 77
Corrosion inhibitors for air-conditioning equipment 50
Corrosion of aircraft metals 56
Corrosion of steel, prevention by surface treatment 52
Corrosion-pitting of steels in fresh water 50
Cosines, sines and, circular and hyperbolic, for radian arguments, tables 70
Cotton, acidic properties 60
Cotton fibers, microscopic examination, in cuprammonium hydroxide solutions 51, 61
Cotton fibers, pectic substance, in relation to growth 73
Cotton, pectic substance in relation to properties of fiber 42
Counters, tube, integrating circuit 78
Coverings, floor, performance tests 24, 42

Page

Cuprammonium hydroxide solutions, use in microscopic examination of cotton fibers 51, 61
Curl tester, paper 41
Cyanide plating baths 36, 77

D

Decomposition of rocks and ceramic materials for chemical analysis 75
Dellinger, J. H., elected chairman, American Section, International Scientific Radio Union 47
Dental silicate cement 58
Deuterium oxide, heat and free energy of formation 34
Diaphragm capsule, aneroid 9
Diaphragms, corrugated metal, for aircraft pressure-measuring instruments 8
Diazomethane, reaction of silk fibroin with 89
Difructose anhydride III, structure of 19
Discharge coefficients of flow nozzles 96
Dispersion, specific, and refraction, of glasses 109
Distillation, azeotropic, in separating petroleum hydrocarbons 107
Drying textile yarns 89
"Dunstone" wall construction 32

E

Eaves trough and conductor pipe, simplified practice recommendation 44
Eclipse, effect (of annular solar, of April 7, 1940) on ionosphere 47
Eclipse, solar, of October 1, 1940 83, 99
Eclipses, solar, and radio critical frequencies 18
Electric contacts, silver 36
Electric fences, safety rules 49
Electric supply stations, safety rules 65
Electric utilization equipment, safety rules 40
Electrical properties of marble 25
Electricity and light, new units 1
Electrode potential, standard, of sodium 107
Electrodeposition, technical practice, and the theory of the potential 18
Electrodialysis for estimating ash in textile fibers 59
Electroplating, composition of cathode films 57
Enamel coatings, porcelain, thickness of acid-resisting portion 49
Enamels, porcelain, color test 109
Energies of isomerization of the five hexanes 76
Energy relations in lead storage batteries 35
Equipment for air-conditioning of materials 51
Exposure tests, outdoor, of nickel and chromium coatings 36

F

Federal screw thread standards 31
Fences, electric, safety rules 49
Fiber building boards, stability 60
Fiber, properties, in relation to pectic substance in cotton 42
Fibers, cotton, microscopic examination, in cuprammonium hydroxide solutions 61
Fibers, silk, X-ray studies 74
Fibers, textile, moisture relations at elevated temperatures 51, 61
Fibroin, silk, reaction with diazomethane 89
Files and rasps, simplified practice recommendation 69

Page

Film, liquid, thickness of adhering 76, 92
Filter paper supply in United States 95
Fire resistance requirements, evaluation 13
Flood waves, laws of travel 3
Floor construction, "Tilecrete Type A" 80
Floor coverings, performance tests 24, 42
Floors, steel, "Scot-Bilt", prefabricated 69
Flow, transition from laminar to turbulent 86
Fluids, volumeters for measuring 58
Frame wall and partition constructions, "Precision-built" 69
Frequencies, radio critical, and solar eclipses 18
Frequency, standard, changes in broadcasts 47
Frequency, standard, revised broadcasts 105
Frost action on bricks, relation of pore system 109
Fuel, aviation, optimum 7
Fuel oils, revised commercial standard 52
Fuel requirements of 1939 automobiles 17
Fungicides, silver in 36
Furfural, reaction of bromire width 19

G

Gage, U. S. Standard, for sheet and plate iron and steel 17
d-galacturonic acid, improvements in preparation 66
Gamma radiation from radium, measurement by free air ionization chamber 25
Germanium, infra-red arc spectrum 7
Glass in portland cement clinker 5, 75
Glass phase in heated clay materials 58
Glasses, specific refraction and dispersion 109
Glasses, sun, commercial standard 44
Glassware, chemical, removal of static charge 66
Grain size, austenitic, effect of heating rate 66
Granites, building and monumental, properties 68
Grounds on water pipes 106

H

Hardware, builders' (nontemplate), commercial standard 91
Hardwood interior trim and molding, commercial standard 15
Heat and free energy of formation, of deuterium oxide 34
Heat, effect of, in light tests 42
Heating and cooling, effect on permeability of masonry walls 25
Heating, effect of rate, on austenitic grain size 66
Heptane, boiling point 25
Hexanes, five, energies of isomerization 76
High-voltage laboratory, new 39
Holbrook, F. S. (Death of) 23
Horological Institute of America, meeting (May 19–20, 1940) 48
Hosiery lengths and sizes 90
Humidity, effect on strength and elongation of silk yarns 110
Hydrocarbons, aliphatic, physical properties 7
Hydrocarbons from kerosene 35
Hydrocarbons, isolation from petroleum 42
Hydrocarbons, petroleum, azeotropic distillation in separating 107
Hydrogen permeability of elastic polymers 74

I

Page

Ice-cream brick molds and cartons, simplified practice recommendation 92
Inductance, dual bridge for measurement 59
Industrial uses for silver 2, 36, 77
Infrared arc spectrum of germanium 7
Inks, new circular on 92
Instruments, pressure-measuring for aircraft, corrugated metal diaphragms for 8
Insulating boards, "Celotex" 52
Insulation, ceiling, effectiveness 88
Insulite wall and partition constructions, structural properties 15
Integrating circuit for tube counters 78
Ionization chamber, free air, for measuring gamma radiation from radium 25
Ionization constant, second, for malonic acid 26
Ionosphere, recombination and electron attachment in the F layers 98
Ionosphere storms and radio transmission between North America and Europe 63
Ionospheric characteristics and radio transmission, reliability of predictions 47
Iron-carbon alloys, critical cooling rate 50
Iron, first spectrum, pressure effect in 34
Isomerization, energies, of the five hexanes 76
Iso-octane, boiling point 25

J

Joints, soft soldered, in copper tubing 96
Journal bearings, load-carrying capacity 40

K

Kerosene, hydrocarbons from 35
Knap concrete wall units 43
Knock rating requirements of 1939 automobiles 17

L

Laminar flow, transition from, to turbulent 86
Lath, "Red Stripe", in wood-frame building constructions 24
Leather, determination of moisture in 100
Leather, stability at elevated temperatures 67
Leather, tensile strength and stretch 68
Legal weights in pounds per bushel for various commodities 31
Length changes, whiteware clay and body 57
Light and electricity, new units 1
Light tests, effect of accompanying heat 42
Lights and signaling equipment for motor vehicles, commercial standards 102
Lime-ferric oxide-silica, the system 86
Liquid film, adhering, thickness 76, 92
Lithography, offset, multicolor, conditioning paper for 15
Load-carrying capacity of journal bearings 40
Low temperatures, effect on properties of aircraft metals 106
Lumber Standards, American 61
Luminous preparations, portable brightness meter 85
Lyxosides, methyl, alpha and beta 19

M

Machine for testing brake linings 40
Malonic acid, second ionization constant 26

Page

Marble, effect of bronze on 6
Marble, electrical properties 25
Masonry walls, permeability, effect of heating and cooling 25
Masonry walls, watertightness 4
Mathematical tables, computation 28, 37
Mathematical tables, sines and cosines 70
Mathematical tables, sines and cosines, for radian arguments 101
Metallic roofing for low-cost house construction 69
Metals, aircraft, corrosion 56
Metals, aircraft, effect of low temperatures on properties 106
Meter, brightness, portable, for luminous preparations 85
Meter, rate-of-flow, for variable discharges 41
Meters, fluid, ASME tests 58
Methyl lyxosides, alpha and beta 19
Micromanometer of the pointer gage type 97
Microphones, absolute pressure calibrations 97
Microscopic examination of cotton fibers in cuprammonium hydroxide solutions 51, 61
Mileage of automobiles, effect on octane number requirement 17
Moisture conditions in concrete 87
Moisture expansion of ceramic whiteware 88
Moisture in leather, determination 100
Moisture penetration through masonry walls 4
Moisture relations of textile fibers at elevated temperatures 51, 61
Molding, hardwood, commercial standard 15
Molds and cartons, ice-cream-brick 92
Monumental granites, properties 68
Mortars, refractory, strength 43
Mortars, test, vibrators for fabricating 14
Munlock dry wall brick masonry wall construction 79
Munson-Walker reducing sugar values, redetermination 41
Musical pitch, standard, changes in broadcasts 47, 105
Mutual inductance, bifilar 49

N

National Concrete Masonry Association, meeting 24
National Conference on Weights and Measures 40
News Letter, Weights and Measures 84
Nickel and cobalt, effects in storage batteries 85
Nickel coatings, outdoor exposure tests 36
Nipples, pipe, commercial standard 91
Nozzles, flow, discharge 96

O

Octane number requirement, effect of automobile mileage on 17
Oil burners, automatic mechanical draft, commercial standard 8
Osmiridium, solution in acids at high temperatures 108
Outdoor exposure tests of nickel and chromium coatings 36

P

"Pack" method for compressive tests of thin materials 78
Painting, effect on sound absorption of acoustic materials 43
Painting of steel, effect of surface treatment 52
"Palisade Homes" wood-frame wall constructions 44
Paper, conditioning, for multicolor offset printing 15
Paper curl tester 41

Page

Paper, filter, supply in United States 95
Paper industry, use of spectrophotometers 34
Paper, size of pores 33
Papers, sheathing, stability 15
Partition construction, frame, "Precision-built" 69
Partition construction, wood-frame, using "Celotex" insulating boards 52
Partition constructions, "Insulite", structural properties 15
Paving brick, simplified practice recommendation 91
Pectic substance of cotton fibers 42, 73
Permeability of elastic polymers to hydrogen 74
Permeability of masonry walls, effect of heating and cooling 25
Petroleum fractionation, properties, of 2,2,4,4-tetramethylpentane 49
Petroleum hydrocarbons, separation by azeotropic distillation 107
Petroleum, isolation of hydrocarbons 42
"Pfeifer units" wall construction 32
Photocells, barrier-layer, photometric procedure using 107
Photochemistry of sheet materials 42
Photoelectric reflectometer, a multipurpose 99
Photometric procedure using barrier-layer photocells 107
Photometric units, new 1
Physical Society, American, 234th meeting 39
Pipe coatings, inspection 16, 96
Pipe-line joints, bonding, for cathodic protection 106
Pipe nipples, commercial standard 91
Plastic calking materials 32
Plastics, water absorption by 74
Plate, iron and steel, U. S. Standard Gage 17
Plating baths, cyanide 36, 77
Plumbing fixtures, measurement of variable discharge 41
Polymers, elastic, permeability to hydrogen 74
Porcelain enamel coatings, thickness of acid-resisting portion 49
Porcelain enamels, color test 109
Pore system in bricks in relation to frost action 109
Pores, size of, in paper 33
Portland cement clinker, glass in 5, 75
Potential theory of, in electrodeposition 18
"Precision-built" frame wall and partition constructions 69
Prefabricated wood-frame constructions 79
Pressure differential, micromanometer for measuring 97
Pressure effect in first spectrum of iron 34
Printing, multicolor offset, conditioning paper for 15
Protein, wool, combination with acid and base 26, 99

R

Radian arguments, tables of sines and cosines 101
Radio communication, amateur, prediction of useful distances 64
Radio critical frequencies and solar eclipses 18
Radio frequency transmissions, standard 47
Radio installations, safety rules 19
Radio societies meetings, April 26, 1940 47
Radio sonde, improvements 78
Radio transmission and ionospheric characteristics, reliability of predictions 47
Radio transmission between North America and Europe, effect of ionosphere storms 63

Page

Radio transmitting station destroyed by fire 105
Radio weather station 64
Radium, gamma radiation, measurement 25
Rasps, files and, simplified practice recommendation 69
Rate-of-flow meter for variable discharges 41
Recombination and electron attachment in the *F* layers of the ionosphere 98
"Red Stripe" lath in wood-frame building constructions 24
Reducing powers of sugars 27
Reducing-sugar values, Munson-Walker, redetermination 41
Reflectometer, photoelectric 99
Refraction and dispersion of glasses 109
Refractory materials, solution in acids at high temperatures 108
Refractory mortars, strength 43
Residential occupancies, fire-resistance requirements 13
Resistance measurements, precise 65
Resistors, standard, comparisons 65
Rocks, decomposition for chemical analysis 75
Roofing, metallic, for low-cost house construction 69
Roofs, steel, Scott-Bilt" prefabricated 69
Rubber, synthetic 66

S

Safety rules for electric fences 49
Safety rules for electric supply stations 65
Safety rules for electric utilization equipment 40
Safety rules for radio installations 19
"Scot-Bilt" prefabricated sheet-steel walls, floors, and roofs 69
Screw thread standards for Federal services 31
Sericin in raw silk 33
Sheathing papers, stability 15
Sheet iron and steel, U. S. Standard Gage 17
Sheet materials, photochemistry 42
Shellac varnish, nonvolatile matter in 88
Shingles, asphalt, weathering tests 110
Signaling equipment for motor vehicles, commercial standards 102
Silicate cement, dental 58
Silicate of soda in refractory mortars 43
Silk fibers, X-ray studies 74
Silk fibroin, reaction with diazomethane 89
Silk, raw, sericin in 33
Silk yarns, strength and elongation, as affected by humidity 110
Silver, corrosion resistance 2
Silver, industrial uses 2, 27, 36, 77
Simplified practice recommendation for eaves trough and conductor pipe 44
Simplified practice recommendation for files and rasps 69
Simplified practice recommendation for ice-cream-brick molds and cartons 92
Simplified practice recommendation for lumber 61
Sines and cosines, circular and hyperbolic, for radian arguments, tables 70
Sines and cosines for radian arguments, tables of 101
Sodium, standard electrode potential 107
Soil-corrosion cells, electrode potentials and polarization 85
Solar eclipse, annular, of April 7, 1940, effect on ionosphere 47
Solar eclipse of October 1, 1940 83, 99
Solar eclipses and radio critical frequencies 18

Page

Soldered joints, soft, in copper tubing 96
Solution of refractory materials in acids at high temperatures 108
Solvent, Stoddard, commercial standard 90
Sonde, radio, improvements 78
Soot, effect of, on rating of heating boilers 90
Sound absorption of acoustic materials, effect of painting 43
Spectrographs, eclipse 83
Spectrophotometers, use in paper industry 34
Spectrum, arc, infrared, of germanium 7
Spectrum of iron, first, pressure effect in 34
Spectrum of tin 18
Spectrum, second, of vanadium 56
Spot test for thickness of chromium coatings 57
Stability of base-metal thermocouples 18
Stability of fiber building boards 60
Staining of marble by bronze 6
Standard frequency broadcasts 47
Standard frequency broadcasts, revised 105
State utility commission engineers, conference, 1940 48
Static charge, removal from chemical glassware 66
Steel, surface treatment, prior to painting 52
Steel wall construction, Bender, structural properties 4
Steel walls, floors, and roofs, "Scot-Bilt" prefabricated 69
Steels, austenitic grain size, effect of heating rate 66
Steels, chromium-vanadium, thermal expansion 3
Steels, corrosion-pitting in fresh water 50
Stoddard solvent, commercial standard 90
Storage batteries, effects of cobalt and nickel 85
Storage batteries, energy relations 35
Sugar, reducing, redetermination of Munson-Walker values 41
Sugars, reducing powers 27
Sulfuric acid, thermochemical properties 35
Sun glasses, commercial standard 44
Supply stations, electrical, safety rules for installation and maintenance 65
Surface colors 27
Surface treatment of steel prior to painting 52
Synthetic rubber 66
System lime-ferric oxide-silica 86

T

Tables, mathematical, computation 28, 37
Tables, mathematical, sines and cosines 70
Tensile test of leather, effect of speed of pulling jaws 68
Tetramethylpentane, properties 49
Textile fibers, estimation of ash by electrodialysis 59
Textile fibers, moisture relations, at elevated temperatures 51, 61
Textile yarns, drying 89
Thermal expansion of chromium-vanadium steels 3
Thermocouples, base-metal, stability 18
Thermocouples, calibration at low temperatures 86
Thickness of acid-resisting portion of porcelain enamel coatings 49
Thickness of adhering liquid film 76, 92

Page

Thickness of chrominum coatings, spot test 57
Thin materials, compression tests, "pack method" 78
Threads, screw, standards for Federal services 31
"Tilecrete Type A" floor construction 80
Timekeeping through the ages 92
Tin, first spectrum 18
Tourmaline crystal, piezoelectric modulus 97
Transfer instrument, ac-dc for standard electrodynamic wattmeter 98
Tube counters, integrating circuit 78
Tubing, copper, soft-soldered joints in 96
Turbulent flow, transition from laminar 86
Typewriter ribbons and carbon paper 61

U

U. S. Standard Gage for sheet and plate iron and steel 17
Units of electricity and light, new 1
Uronic acid, determination, in cellulosic materials 7
Utility commission engineers, State, conference, 1940 48
Utilization equipment, electric, safety rules for installation and maintenance 40

V

Vacuum-tube alternating-voltage compensator 59
Vanadium, chromium, steels, thermal expansion 3
Vanadium, second spectrum 56
Vapor lock requirements of 1939 automobiles 17
Varnish, shellac, nonvolatile matter in 88
Vibrators for fabricating test mortars 14
Volumeters for measuring fluids 58

W

Wall construction, Bender steel 4
Wall construction, concrete, Knap 43
Wall construction, "Dunstone" 32
Wall construction, frame, "Celotex" insulating boards 52

Page

Wall construction, frame, "Precision-built" 69
Wall construction, "Insulite" 15
Wall construction, "Munlock" dry wall brick 79
Wall construction, "Pfeifer units" 32
Wall construction, steel, "Scot-Bilt" 69
Wall constructions, brick-concrete-block and concrete-block, tests 5
Walls, masonry, permeability, effect of heating and cooling 25
Walls, masonry, watertightness 4
Water absorption by plastics 74
Water pipes, grounds on 106
Watertightness of masonry walls 4
Wattmeter, standard electrodynamic and ac-dc transfer equipment 98
Waves, flood, laws of travel 3
Waves, irrotational translation 3
Weather station, automatic 64
Weathering tests of asphalt shinges 110
Weighing and measuring apparatus for Brazil 84
Weights and Measures, Henry W. Bearce heads Division 40
Weights and Measures, National Conference (Thirtieth) 40, 55
Weights and Measures News Letter 84
Weights in pounds per bushel for various commodities 31
Whiteware clay and body length changes 57
Whiteware, ceramic, moisture expansion 88
Windows, air infiltration through 61
Wood-frame construction, "Celotex" insulating boards 52
Wood-frame construction, "Palisade Homes" 44
Wood-frame construction, prefabricated 79
Wood-frame construction, "Red Stripe" lath 24
Wool protein, combination with acid and base 26, 99
WPA mathematical tables 28

X, Y, Z

X-ray laboratory, new 39
X-ray measurements up to 1,500,000 volts 25
X-ray studies of silk fibers 74
Yarns, silk, strength and elongation 110
Yarns, textile, drying 89
Yield strength, a rational definition 3

U. S. GOVERNMENT PRINTING OFFICE: 1940